












Dimensions 3.74* Unit: Inch (mm)















2.1_{MP} Resolution Intelligent Video

Analytics

Star-Light Plus™

2.8mm Fixed Lens

Summary

This NDAA-compliant MEGApix® IP camera provides 2.1MP/1080p resolution at real-time 30fps, includes a 2.8mm fixed lens and simultaneous H.265/H.264/MJPEG codec support. The camera is powered by Star-Light Plus™ color in near-total darkness technology for quality video in any lighting conditions. The weather-resistant vandal ball turret cameras are IP67 rated, eliminate IR reflections and offer easy angle adjustment for optimal image quality. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- 2.8mm fixed lens
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Vandal ball turret housing reduces IR reflection with true 90° tilting and 360° rotation
- Smart DNR[™] 3D digital noise reduction
- True day/night mechanical IR cut filter
- · Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- · Motion detection
- PoE class 3 and DC12V
- UL listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- · 5 year warranty



Accessories (Optional)



DWC-PMB-WL-W Pole mount



DWC-V1CNMW Corner mount



DWC-VACM Ceiling mount bracket



DWC-VAJUNC Junction box DWC-VAWM Wall mount bracket

Specifications





IMAGE Image conser	21MD/1090p 1/29" CMOC
Image sensor	2.1MP/1080p 1/2.8" CMOS
Total pixels	1945 (H) X 1109 (V)
Minimum scene illumination	0.05 lux (color) 0.0 lux (B/W)
LENS	O.O ldx (B) W)
Focal length	2.8mm, F2.0
Lens type	Fixed lens
HFOV / VFOV	110° / 59°
IR distance	100ft range
OPERATIONAL	looit range
OPERATIONAL .	IVA: intrusion, line crossing, counting line, loitering, enter, exit
Intelligent Video Analytics	tamper (DWC-MVA2Wi28T) IVA: object removed, tailgating, direction, stopped, appear disappear, object left, logical rules (DWC-MPVA2Wi28T)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 ~ 1/32000
Slow shutter	1/2,1/3,1/5,1/6,1/7.5, 1/10
Auto gain control	Auto
Day and Night	Auto, day (color), night (B/W)
3D digital noise reduction	Smart DNR™ 3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Backlight compensation (BLC)	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail and FTP server recording
NETWORK	Trouncations via e manaria i ii server recording
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
video compression type	H.265: 2.1MP/1080p, 720p, VGA, D1, CIF
Resolution	MJPEG: 1280x720, 800x600, VGA, D1, CIF MJPEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps ~ 10Mbps, multi-rate for preview and recording
Bitrate control	Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPVI/V2/V3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
	OS: Windows®, Mac® OS, Linux®
Web viewer	Browser: IE*, Google Chrome*, Mozilla Firefox*, Safari* NOTE: Chrome browser is recommended for IVA configuration
Video management software	DW Spectrum* IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F ~ 122°F (-20°C ~ 50°C)
Operating humidity	10-90% (non-condensing)
IP and IK rating	IP67-rated , IK10 impact-resistant
Other certifications	UL listed, CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE IEEE 802.3af Class 3. (Adapter not included)
Power consumption	DC12V: max 5.7W PoE: max 7.2W
MECHANICAL	
Material	Aluminum vandal ball turret housing
Dimensions	4.92" x 4.8" (125 x 122 mm)
Weight	1.76lbs (0.8kg)
Warranty	5 years warranty



Built for Users.









